APPLICATIONS



Home decoration



Sinage



Crafts



Digital products

GIBSON IMAGE

GIB 3220 UV Flatbed Printer



sistemasysoluciones


Av. Belgrano 748 - Piso 4 Oficina 43 C.A.B.A. - C1092AAU - Argentina info@sistemasysoluciones.com Tel/Fax: (011) 4342 5742 www.sistemasysoluciones.com




GIBSON UV Flatbed Printer

The GIBSON UV flatbed printers are the perfect solution for indoor,outddor,fine art and industrial applications.

Real industrial level machine which can meet the needs for customized orders with high performance.



MACHINE DETAILS



Gear stepping system with encoder

Gear stepping system at Y axis by both sides to make sure easy installation, with encoder for high precision



Linear motor

Optional linear motor boost scan speed and productivity more stable movement and easy maintennance



High quality steel structure

Enhanced steel structure,multiple stress-relieve treatment to prevent from deforming



Anti-crash

shuttle safety sendors on each side protects the valuable print heads by preventing them from hitting the media in case of emergency



Negative pressure

Automatic negative pressure system with safety design & stable output

- · Continuous printing after power off
- · 5 layers printing
- \cdot 3D embossed effect
- . UL standard $\,$



Automatic height measurement

Intelligently detect printed material thickness, ensure high performance printing













PRINTING EFFECT




White Upper-layer



Image A-White-Image B



5 layers printing



White Under-layer



Embossed printing



White-color-varnish

TECHNICAL SPECIFICATION

TECHNICAL	DIECHTCATION	
Model	GIB3220	
Printhead	Ricoh Gen5 7-14-21 PL	Ricoh Gen6 5-10-15 PL
Color mode	K C M Y Lc Lm W Varnish / Primer	
Max. material thickness	0~100mm	
Printing size	3200mmx2000mm	
Billboard speed	50 m²	63 m²
Production speed	31 m²	41 m²
Quality speed	23 m²	32 m²
Curing system	UV LED lamp	
Ink type	UV Curing ink	
Ink capacity	3L drums, automatic surveilance for shorting of ink, non-stop add ink	
Ink supply system	Auto negative ink supply	
Media	Glass, Acrylic, Ceramic, Metal, Paper, Wood, Leather, Flex banner,	
	Wallpaper,Car sticker,Soft film,PVC,PP,PE,PTFE	
RIP software	Onyx , Caldera	
Working condition	Humidity 38%-60% RH, Temperature 15°C-28°C, ventilation and low dust,	
	avoid direct sunlight	
PC system	Windows 7, Windows 10	
Power supply	6.5KW,single phase AC200~240V,50/60HZ,32A	
Dimensional(LxWxH)	5350mm x 2500mm x 1600mm	
Weight	1800KG	
Safety certification	CE certification	

Above specifications are subject to change without prior notice.