

INTELLIGENT CARRIAGE VISUAL POSITIONING FUNCTION



DLI-2513/1612



Application industry



badge



acrylic



souvenir



accessories

Technical Parameters

Mode of Equipment	DLI-2513/1612 carriage visual faltbed	Printing Size	2500*1300mm/1600mm*1200mm
Camera range	2400mm*1200mm/1500*1135mm	Camera lifting height	0-200mm
Identification system	Carriage scanning system	Print head type	Ricoh G5/G5S/G6 Epson i3200/i1600
Printing color	CMYK+LCLM+W+V	RIP Software	Riprint
Printing Height	0-200mm(could be customized)	Printing Precision	960*900DPI/960*1200DPI/960*1800DPI
Data interface	Gigabit network interface	Power requirements	AC220V(±10%); 50HZ;P:8000W
Driver Software	Microsoft Windows 10 pro	File format	TIFF(RGB&CMYK)BMP、PDF、EPS、JPEG、etc.
Operation Environment	Temperature:20°C-32°C /Humidity:40-70%		
Print head quantity	Ricoh G5/G6,2-8(could be customized) Epson2-6(could be customized)		
Ink System	Continuous ink supply/ink tank 2000ml/subtank constant temperature and pressure/white auto stirring		
Printer Weight	1700KG/1390KG (weights are diffrent from different configurations)		
Printer Dimension	4590mm*2180mm *1450mm / 3730mm*1970mm*1450mm		