SCORPID SERIES - DIGITAL LABEL FINISHING SYSTEMS

RoHS CE




The digital label finisher with no lamination module ideal for those who use pigment-based ink / laser technology printers (water and fade resistant).



The ideal companion to 8.5" digital color label printers





digital color label presses

Full flexibility, limitless variations in label design and smooth workflow.

The Scorpio Series are digital label finishers truly meant to meet the on-demand short run label finishing solution for use with digital color label printers and presses.

The Scorpio Series are all-in-one systems that unwind, laminate with laminate liner rewind core holder for labels added durability (only SCR22PL and SCR35PL), digitally die-cut, remove the excess label material around each die-cut shape, slit, and rewind offering you everything to professionally cut and finish labels.

All systems provide a very accurate label finishing solution using cutting plotter technology.

This allows you to cut different types of material and shapes on the fly without the added cost of dies.

The units are equipped with a cutter management tool that works together with a camera forming an integrated optical blackmark registration system providing cutting speed optimization and avoiding synchronization issues.

SCORPIO SERIES - DIGITAL LABEL FINISHING SYSTEMS

Rohs CE

SCORPIO CUTTING MANAGER

Scorpio software works together with a camera forming an integrated optical black-mark registration system.

With this software, the operator can import the cutting files created on Adobe Illustrator, Inkscape or Corel Draw which is also used to create the black marker.

The Scorpio is equipped with a camera used to detect the black-mark printed on the media. This camera assist the software in detecting the black-mark created inside the cutting file.

This process tells the plotter when and where to start cutting the media.

 Scorpio - Digital Finishing System Advanced - 		- 0 ×
PDF preview:	Forward media	Backward media
Offset X	Black-Mark mode Distance between Black-Marks (mm): 70	Blank mode
	Black-Mark 2mm	Step (mm): 5
Offset Y 0 mm	Cutting force 7 Cutting speed (mm/s) 600	Copy mode On/Off 2 Copies: 0 1
Job completed Open PDF Open last job	Start P	ause Cut test

Cutting manager tool.



Camera





Core holder's clutch



Waste matrix removal



the first

Tension arm



Slitting



Laminating (SCR22PL and SCR35PL only)



Adjustable clutch



Shelf

SOME BENEFITS OF USING THE SCORPIO SERIES:

- » Short run label production in-house means reducing inventory requirements and costs
- » Producing full bleed labels will no longer be a nightmare
- » Laminating for labels added durability (no need for special media)
- » No need to order pre-die cut label rolls
- » No need for ultra-precise label margin adjustment when printing in full bleed
- » No need to set up a minimum gap between labels when printing in full bleed (saving on media).

SCORPIO SERIES - DIGITAL LABEL FINISHING SYSTEMS

RoHS COMPLIANT 2002/95/EC CE

WHAT SCORPIO SERIES HAVE AND THE COMPETITION DOESN'T		
Optical Sensing	Scorpio series use a camera forming an integrated optical black-mark registration system allowing to read one black-mark for each cutting layout. Optimizing cutting speed. No synchronization issues.	
Adjustable Clutch	This feature allows to obtain flat tight finished rolls and waste material neatly rewound.	
Size Does Matter	Scorpio series size help operators have more room to easily and quickly load the media and get the machine ready to work in a few minutes.	
Media Track	Scorpio series are equipped with an ultrasonic sensor system that generates a loop of media both in plotter input and output in order to guarantee a smooth media track during the cutting operations.	
Slitter Blades	Scorpio series are equipped with inexpensive multi edge blades. Blade life extended 4 times as much.	
Blank Labels	Scorpio seires can cut blank labels. Through the Scorpio software, operators only need to set label step. No printed black-mark required on the media.	
Software	Software can be installed on any computer running Windows 8.1 or later. Not supported by macOS systems.	
Media	Scorpio series allow to use any media from 100mm (4") up to 355mm (14") wide.	
Matrix Rewinding	Scorpio series feature synchronized motorized core holders that avoid any matrix tear while removing and rewinding.	
Easy To Move	Scorpio series are equipped with four wheels that allow to easily move the machine.	
Remote Assistance	Customers whose computers are connected to internet can be reached by one of our operators for remote assistance and firmware upgrades.	





ACCESSORIES INCLUDED

Our digital finishing systems equipped with a removable drawer (only SCR22PL and SCR35PL) and a roller positioned above the core holder to help rewind the compressed waste.

This design makes the unit more practical and helps it avoid the most common the issues of rewinding.

All devices have also the o-rings on the matrix remover roller, used to facilitate the removal of your matrix from the labels.



SCORPIO SERIES - DIGITAL LABEL FINISHING SYSTEMS

Rohs CE

Part number SCR22 SCR22PL SCR35 SCR35 Input / Output max. roll diameter 250mm (9.84") 355mm (9.85") 355mm (9.85") 330mm (9.7") 330mm (9.7") 330mm (9.7") 300m	(4.25")			
Minimum media width 108mm (4.25") 108mm (4.25") 108mm (4.25") 108mm (4.25") Maximum media width 225mm (8.86") 225mm (8.86") 355mm (14") 355mm Maximum cutting width 200mm (7.87") 200mm (7.87") 330mm (13") 330mm Minimum slitting width 19mm (0.75") 19mm (0.75") 19mm (0.75") 19mm (0.75")	(4.25")			
Maximum media width 225mm (8.86") 225mm (8.86") 355mm (14") 355mm (14") Maximum cutting width 200mm (7.87") 200mm (7.87") 330mm (13") 330mm (13") Minimum slitting width 19mm (0.75") 19mm (0.75") 19mm (0.75") 19mm (0.75") Number of slitting blades up to 8 up to 8 up to 13 up to 13	n (14")			
Maximum cutting width200mm (7.87")200mm (7.87")330mm (13")330mmMinimum slitting width19mm (0.75")19mm (0.75")19mm (0.75")19mm (0.75")19mm (0.75")Number of slitting bladesup to 8up to 8up to 13up to 13	. ,			
Minimum slitting width19mm (0.75")19mm (0.75")19mm (0.75")19mm (0.75")Number of slitting bladesup to 8up to 8up to 13up to 13	(13")			
Number of slitting blades up to 8 up to 8 up to 13 up to 13				
	(0.75")			
Lamination module NO YES NO YES	3			
Dimensions $H = 145 \text{ cm} (57.06")$	0 cm (78.74") 5 cm (57.06") cm (27.56")			
Weight (estimated) 180 kg (396 lb) 235 kg (518 lb) 200 kg (441 lb) 245 kg	(540 lb)			
Roll core size 76mm (3")				
Minimum / Maximum label length 10mm (0.39") / 450mm (17.71")				
Maximum media thickness 0.25mm (10 mil)				
Maximum cut speed 600mm/s (24 in/s) in all directions	600mm/s (24 in/s) in all directions			
Cut precision 0.3mm (0.012")	0.3mm (0.012")			
Warranty One year parts and labor. Usage limitation may apply	One year parts and labor. Usage limitation may apply			
PLOTTER SPECIFICATIONS				
Data interface USB 2.0				
Linear cut speedDependent on graphic2 squares across 80x80mm (3.15"x3.15") = 34 labels per min.				
Programmable Cutting Force 20 gf - 300 gf in 31 steps (Max 300 gf)	20 gf - 300 gf in 31 steps (Max 300 gf)			
Test cut function Yes	Yes			
Cut to registration Single point registration black-mark (4mm (0.16") or 2mm (0.08") square)	Single point registration black-mark (4mm (0.16") or 2mm (0.08") square)			
Cut ability Both printed and unprinted media	Both printed and unprinted media			
Interface & Software Scorpio proprietary software can be installed on any computer running Will later. Not supported by macOS systems.	Scorpio proprietary software can be installed on any computer running Windows 8.1 or later. Not supported by macOS systems.			
	100-240 VAC, 240 watts			