



SINAJET
Cut better



CHANGZHOU SINAJET SCIENCE AND TECHNOLOGY CO.,LTD.

TEL: 0086 519 86683500

FAX: 0086 519 86801276

E-mail:sales@sinajet.cn

P.C:213161

Address:No5. Xinya Road, Wujin High-tech Industrial Zone Changzhou,
Jiangsu Province, China

SINAJET ALL RIGHTS RESERVED, THIS CATALOGUE FOR YOUR REFERENCE ONLY.
IF THERE IS FLUCTUATION, ACCORDING TO THE REAL OBJECT PLEASE.

SINAJET
Cut better

Digital Cutter

**Fasting Printing, Graphic,
Small Package Cutting Solutions**

www.sinajet.cn



Digital Cutter

Fastest Printing, Graphic,
Small Package Cutting Solutions



SOLUTIONS



Advantages

- 1 / Modular cutting tools design makes more materials can be cut.
- 2 / Clean and humanized mechanical machine design, focus on operators' easy operation and after sales service.
- 3 / Effective cutting area is can cover cutting material up to size A10 and B10
- 4 / Automatic lifting feeding platform together with the vacuum clamps load each sheet to the conveyor table for continuous cutting process.

Parameters

Model	DF0604 / DF0906 / DF1007	DF0604-MT / DF0906-MT / DF1007-MT / DF0912-MT / DF1216-MT
Installed Tools	Rotary Knife,CCD,Crease Wheel, Pen(Needle),Crease Wheel	Drag Knife,Active Circular Knife,V-Cut,Kiss Cut,Auto Depth Device
Optional Devices	NO	Oscillating Knife,Active Circular Knife,V-Cut,Kiss Cut,Auto Depth Device
Cutting Thickness	≤1.5mm (depends on cutting materials)	≤1cm (depends on cutting materials)<2cm (DF0912-MT/1216-MT)
Cutting Material	Card Paper, PP Paper, Sticker	Card Paper, PP Paper, Sticker,KT Board, Foam Board,ABS Board, Grey Board, Corrugated Paper, Reflective Material
Active Cutting Area	600(L)*400(W) mm / 900(L)*600(W) mm / 1000(L)*700(W) mm / 900(L)*1200(W) mm / 1200(L)*1600(W) mm	Conveyor Table
Working Table		Holding and Feeding by Vacuum Suckers
Material Feeding Method		Barcode reader & QR code reader
Barcode Reader		1400mm/s
Max Cutting Speed		1000mm/s
Max Single Axis (X or Y) Cutting Speed:		±0.1mm
Cutting Repeat Accuracy		DXF, HPGL, CUT, ISO, PLT, PDF, XML, AI
Allowed File Format		LAN
Data Transmission		220V
Power Supply		1.5KW/2.2KW/5.5KW(DF1216-MT)
Air Pump Power		Temperature 0-40°C, Humidity 20%-80% no condensation
Working Environment		