


6090

UV Flatbed printer


Full range of solutions to meet your production needs, high performance flatbed UV printer.

I1600/I3200*3




4C+2SP

I3200HD*3



4C+6SP

XP600*3



4C+4SP



Color Set	Features
4C+2SP	High volume production and high speed printing with two spot colors(W,V) added to the four colors C, M, Y and K.
4C+6SP	Four colors C, M, Y and K as well as six spot colors(W,V,Lc,Lm,Or,Gr,Vt,R,Lk,Lik optional) enhance functionality and expressiveness.
4C+4SP	High-quality printing with four spot colors(Lc,Lm,W,V) added to the 4 colors C, M, Y, K .

X6090 print high quality graphics at incredible speeds directly onto 60*90cm media and build a successful customization business with range of application. Provides even more unique printing opportunities for your online store, retail store, sign shop, or other business.

Key Features:

Variable color configuration

—Standard 4-10 colors for your choice. Highly concentrated white ink as the basic color on transparent or deep-color media, add glossy ink and spot color processing to make full color images more vivid.

High accuracy vacuum printing platform

—Made of aluminum plate, internal honeycomb structure with high precision, flatness control within 0.1mm. Whole Vacuum table can be applied maximize air suction in specific areas— enabling easy media loading and print stability.

Intelligent control panel

—Humanized design, in line with human use habits, flexible and simple to operate, and runs safe, clean, and cool.

Advanced Waveform control

—Xenons unique advanced ink droplet ejection control, droplets with high circularity are ejected to make them accurately land on the media, enabling sharp expression of characters, lines, and edges.

Maximum 180mm print height

—The beam can be lifted up to 180mm to meet the printing needs of different media thicknesses.

Motorized cylindrical jig

—Beautiful seamless rotating surface printing with simple step . It can be printed with a diameter of 30-120 mm.

Technical parameters

Model			
Model	X6090		
Print Parameter			
Printhead	I3200	XP600	I1600
No. of Printhead	3		
Max Speed	36 sqm/h	20 sqm/h	18 sqm/h
Quality	10 sqm/h	7 sqm/h	5 sqm/h
Resolutions	2400dpi Max		
Media			
Table Size	600*900mm		
Media thickness	Max.180mm		
Media Specs	Rigid and flexible flat materials; Rotary device as optional.		
Inks			
Type	Environmental friendly UV/LED curable ink		
Ink Supply System	1.5L Large Bulk System with automatic supply system		
Colors	Standard CMYK Lc Lm W V, spot color for optional		
Ink curing system	LED UV Curing System		
Operating Environment			
Software	Standard (SAI photoprint); Onyx, Caldera, Wasatch as optional		
Connectivity	USB 3.0		
Power	Single Phase , 220VAC±10 % , 50 / 60HZ ; 2000W (Machine)		
Environment	Temp. 15-32°C; RH 40-65%		
Dimensions & Weight			
Machine (L*W*H)	1735*1500*610mm		1640*1530*700mm
Package (L*W*H)	1840*1600*900mm, 330kg		1800*1700*1000mm, 330kg

YILIJET GROUP

Facilities 1: Optical Valley, Wuhan, Hubei

Facilities 2: Hi-Tech Industrial Zone, Wuhan, Hubei

Facilities 3: Xian'an Economic Development Zone, Xianning, Hubei

Facilities 4: Zhongxiu Industrial Park, Panyu, Guangzhou

Branches: (Showroom, Sales & Service)

Europe(Brno), Zhejiang(Shaoxing), India(Mumbai), South America(Brasil)